TOA VX-3000PM Preamp Matrix Panel – 8-Input Audio Matrix



0.00 SAR ✓ In Stock

FEATURES :

- 8 Audio Inputs
- 8 Volume Control Knobs
- 20 Control Inputs + 10 Control Outputs
- Connect 1 Unit to Single Frame

TOA VX-3000PM Preamp Matrix Panel	
Power Source	20 - 33 V DC, removable terminal block (2 pins)
Current Consumption	0.33 A at 33 V DC input 0.35 A at 24 V DC input
LAN A, B	Number of Connectors: 2 (LAN A, LAN B) Network I/F: 100BASE-TX Network Protocol: TCP, UDP, ARP, ICMP, RTP, IGMP, HTTP Spanning tree Protocol: RSTP Audio Transmission System: TOA Packet Audio (*1) Audio Encoding Method: PCM Audio Sampling Frequency: 48 kHz Audio Quantifying Bit Number: 16 bits Connection Device: Other VX-3004F, VX-3008F, VX-3016F, NX-300, VX-3000CT, VX-3000PM, Switching HUB Connector: RJ45 connector Connection Cable: Category 5 twisted pair cable (CAT5) or greater Maximum Cable Distance: 100 m
Audio Input	8 inputs Input Level: INPUT 1 - 4: -60 dB (*2) / -40 dB (*2) / -20 dB (*2) / 0 dB (*2) selectable, input impedance 600 Ω, tranformer-balanced INPUT 5, 6: -20 DB (*2), input impedance 10 kΩ, unbalanced INPUT 7, 8: 0 dB (*2), input impedance 10 kΩ, unbalanced Frequency Response: -60 dB (*2): 200 Hz - 10 kHz, -2 dB ± 3 dB -40 dB (*2) / -20 dB (*2) / - dB (*2): 100 Hz - 15 kHz, -2 dB ± 3 dB Distortion: 1 % or less Signal to Noise Ratio: 60 dB or more Removable terminal block (6 pins x 2, 4 pins x 2) Only Input 1 is used in common with the front-mounted ø6.3 mm phone jack
Control Input	20 channels, no-voltage make contact input, open voltage: 30 V DC, short-circuit: 2 - 10 mA Connector: Removable terminal block (10 pins x 2, 12 pins x 2)
Control Output	Channels 1 - 5, relay (a contact), withstand voltage: 30 V DC, control current: 1 A Channels 6 - 10, open collector output (polarized), withstand voltage: 30 V DC, control current 100 mA Connector: Removable terminal block (10 pins) x 2
Indicators	SIGNAL Indicator (Green) x 8, RUN (Green) x 1, LINK/ACT (Green) x 2
Volume Control	8 channels
Operating Temperature	0 °C to +40 °C
Operating Humidity	90 %RH or less (no condensation)
Dimensions (W x H x D)	482 x 44 x 292.4 mm
Weight	3.2 kg

Accessory	Rack mounting screw x 4, Removable terminal plug (6 pins) x 2, Removable terminal plug (4 pins) x 2, Removable terminal plug (10 pins) x 4, Removable terminal plug (12 pins) x 2, Removable terminal plug (2 pins) x 1