# TOA VX-3008F Voice Evacuation Frame – 8-Zone SS System Controller – EN54-16 Certified PA/VA Solution




**0.00 SAR** ✓ In Stock

**FEATURES :**

Model: VX-3008F
Power: 20–33V DC, 4-pin terminal block
Humidity: ≤90% RH (no condensation)
Size: 483 × 132.6 × 345 mm
Weight: 7.9 kg

| TOA VX-3008F Voice Evacuation Frame | |
|---|---|
| Power Source | 20 - 33 V DC, removable terminal block (4 pins) |
| Power Consumption | 24 W (frame only) at 33 V DC input, 90 W (RS Link: 2 A output) at 33 V DC input |
| Indicators | POWER (green) ...1, RUN (green) ...1, EMERGENCY (red) ...1, CPU OFF (red) ...1, LAN A (green) ...1, LAN B (green) ...1, RS LINK A (green) ...1, RS LINK B (green) ...1 FAULT STATUS (yellow) GENERAL ...1, UNIT ...1, NETWORK ...1, EMG MIC ...1, FUSE ...1, POWER ...1, CPU ...1, ZONE ...8 AMPLIFIER PEAK (red) ...3, SIGNAL (green) ...3, OPERATE (green) ...3, POWER (green) ...3 |
| Control Input 1, 2 | 16 inputs, no-voltage make contact input, open voltage: 24 V DC, short-circuit current: 2 mA Fault Detection System: Short circuit, Open circuit, Method: Voltage detect Connector: RJ45 connector Connection Cable: Shielded Category 5 twisted pair cable (CAT5-STP) |
| ATT/Control Output | 8 outputs, no-voltage make contact, relay contact (NC, NO, C), control current: 2 mA to 5 A, withstand voltage: 125 V AC, 40 V DC Connector: Removable terminal block (12 pins) ...2 |
| Compressor | Threshold: -20 to 0 dB (1 dB steps) Ratio: 1:1, 1.1:1, 1.2:1, 1.3:1, 1.5:1, 1.7:1, 2:1, 2.3:1, 2.6:1, 3:1, 4:1, 5:1, 7:1, 8:1, 10:1, 12:1, 20:1, ∞:1 Attack time: 0.2 ms - 5 s, Release time: 10 ms - 5 s Gain: - ∞ to +10 dB, Knee type: hard knee, middle knee, soft knee |
| Modules (*3) | Number of Modules: 3 (When the Line Output module is installed ...2) DA CONTROL LINK ...3 DA OUTPUT LINK ...3 (Used only when a Power Amplifier module is installed) |
| Operating Temperature | -5 ℃ to +45 ℃ (23 □F to 113 □F) |
| Operating Humidity | 90 %RH or less (no condensation) |
| Finish | Panel: Surface-treated steel plate, black, 30 % gloss, paint |
| Dimensions | 483 (W) × 132.6 (H) × 345 (D) mm (19.02 × 5.22" × 13.58")" |
| Weight | 7.9 kg (17.42 lb) |
| Accessory | Rack mounting bracket (preinstalled on the unit) ...2, Rack mounting screw ...4, CD (PC setting software) ...1, Removable terminal plug (2 pins) ...6, Removable terminal plug (4 pins) ...1, Removable terminal plug (6 pins) ...2, Removable terminal plug (12 pins) ...2, Removable terminal plug (17 pins) ...1, Ferrite clamp ...2 |