# TOA VX-3308WM Wall-Mount Voice Evacuation System




**0.00 SAR** ✓ In Stock

**FEATURES :**

The VX-3308WM is a combined PA and VA system based on the VX-3000 system and is certified according to the European Standard EN54-16. It is designed to be wall-mounted requiring little space and can be operated as a stand-alone unit as well as being combined with all VX-3000 units. Due to the scalable and integrated architecture of the VX-3000 system, the VX-3308WM is an ideal solution for distributed locations, for example, to cover the many floors of a high-rise building.

| TOA VX-3308WM Wall-Mount Voice Evacuation System | |
|---|---|
| Power source | 220 - 230 V AC, 50 / 60 Hz Battery 2x 12 V |
| Power / current consumption | 1100 watts (at rated output incl. charging), 460 watts (EN 60065) |
| Frequency response | 40 Hz - 20 kHz |
| Indicator | AC Power in (green) ×1, Run (green) ×1, Emergency (red) ×1, CPU Off (red) ×1, LAN A (green) ×1, LAN B (green) ×1, RS Link A (green) ×1, RS Link B (green) ×1. Fault Status (yellow): General ×1, Unit ×1, Network ×1, EMG Mic ×1, Fuse ×1, Power ×1, CPU ×1, Zone ×8. Amplifier: Peak (red) ×3, Signal (green) ×3, Operate (green) ×3, Power (green) ×3. Battery (green): Charging ×1, Battery power ×1, connection ×1, condition ×1 |
| Connection | AC-mains: 2 pin screw terminal at breaker, 1 screw terminal for earth Speaker outputs: 6-pin removable screw terminal block ×4 Control inputs: 9-pin removable screw terminal blocks ×3 Emergency control inputs: 5-pin removable screw terminal block ×1 Control outputs: 9-pin removable screw terminal block ×1, 12-pin removable screw terminal block ×1 Network: 9-pin removable screw terminal block ×2 Internal connections: DC power supply (max. 25 A): 2-pin screw terminal ×1 DC power supply 24 V DC, 0.3 A: 4-pin removable screw terminal block ×1 |
| Dimensions | 550 x 700 x 200 mm (W x H x D) |
| Finish | Steel plate, black (RAL 9011 or equivalent) |
| Operating temperature | -5 °C to +45 °C (23 F to 113° F) |
| Weight | 33.1 kg |