



1,600.00 SAR ✓ In Stock

FEATURES :

- Tone Frequency: 32.768 kHz
- Oscillator: PLL synthesized
- Maximum Input Level: 126 dB SPL
- Maximum Deviation: ± 40 kHz
- Origin: Japan

System & Receiver Specifications (TOA WT-5810)

Brand & Model	TOA WT-5810 (Space Diversity Tuner)
Frequency Range	UHF Band (576 MHz – 865 MHz, variant/region dependent)
Selectable Channels	64 selectable channels (Up to 16 simultaneous channels in one area)
Tone Frequency	32.768 kHz
Total Harmonic Distortion	< 1% (typical @ 1 kHz with ± 40 kHz deviation)
Operating Range	3 meters to 120 meters line-of-sight
Audio Frequency Response	100 Hz – 15,000 Hz (± 3 dB)
Audio Mixing Output	Balanced XLR: -60 dB, 600 Ω Unbalanced 1/4" Phone Jack: -20 dB, 600 Ω
Power Source	12V DC (130 mA consumption via included AC Adapter)

Handheld Transmitter Specifications (TOA WM-5225)

Brand & Model	TOA WM-5225 (Handheld Transmitter)
RF Carrier Power	Less than 50 mW (ERP preset to 10 mW)
Maximum Input Level	126 dB SPL (Prevents audio clipping/distortion from loud voices)
Battery Requirements	1 $\times$ AA Alkaline battery (1.5V) OR WB-2000 Rechargeable battery
Continuous Run-Time	Alkaline: Approx. 10 Hours WB-2000: Approx. 13 Hours