TOA WT-5810 + WM-5225 UHF Wireless Microphone High Quality



1,600.00 SAR ✓ In Stock

FEATURES :

- Tone Frequency: 32.768 kHz
- Oscillator: PLL synthesized
- Maximum Input Level: 126 dB SPL
- Maximum Deviation: ±40 kHz
- Origin: Japan

TOA WT-5810 + WM-5225 UHF Wireless Microphone

POWER CONSUMPTION	130 mA (12 V DC)
RECEIVING FREQUENCY	576 – 865 MHz (*2), UHF
MIXING OUTPUT	MIC: -60 dB (*1), 600 Ω, balanced, XLR-3-32 type connector LINE: -20 dB (*1), 600 Ω, unbalanced, phone jack
MIXING INPUT	-20 dB (*1), 10 kΩ, unbalanced, phone jack
RECEIVING SENSITIVITY	90 dB or more, Signal to Noise ratio (20 dBμV input, 40 kHz deviation)
SQUELCH SENSITIVITY	16 – 40 dBμV variable
TONE FREQUENCY	32.768 kHz
SIGNAL TO NOISE RATIO	104 dB or more (A-weight, unbalanced output)
HARMONIC DISTORTION	1 % or less (typical)
FREQUENCY RESPONSE	100 Hz – 15 kHz, ±3 dB
OPERATING TEMPERATURE	-10 °C to +50 °C (14 □F to 122 □F)
OPERATING HUMIDITY	30 % to 85 %RH
DIMENSIONS	206 (W) × 40.6 (H) × 152.7 (D) mm (8.11″ × 1.6″ × 6.01″) (excluding antenna)
WEIGHT	590 g (1.3 lb)
ACCESSORY	AC adapter (*3)...1