ZKTeco F35 Fingerprint Time Attendance and Access Control Terminal



680.00 SAR ✓ In Stock

FEATURES :

- Model: F35
- 2.4"@ TFT Color LCD Screen
- Fingerprint capacity: 10,000
- Card Capacity: 10,000 (1:N)
- Fingerprint/Card/Password

Specification

Fingerprint Capacity	10,000 (1:N)
Face Capacity	N/A
ID Card Capacity	10,000 (1:N)
Display	2.4"@ TFT Color LCD Screen (720*1280)
Communication	TCP/IP*1 Wi-Fi (IEEE802.11a/g/n) @ 2.4 GHz Wiegand (Input & Output)*1 RS485: ZKTeco RS485 *1 Aux Inputs *1, Aux Outputs *1, Electric Lock*1, Door Sensor*1, Exit Button*1, Alarm*1, Doorbell*1
Standard Functions	Webserver, ADMS, DST, Up to 14-digit User ID, Access Levels, Groups, Holidays, Anti Passback, Record Query, Tamper Switch Alarm, Multiple Verification Methods Video Door Phone, ONVIF (Compatible with Profile S, Profile T, Profile G, Profile C, Profile Q & Profile A), AC Push and TA Push, Protocol Switch, HTTPS / SSH Backend Access, T9 Keyboard (Input)
Others	Transaction Capacity: 500,000 Biometric Algorithm: ZKFingerprint V10.0 Support Card Type: D Card@125 kHz (Standard) Optional Multi-Tech Module: Module1: ID & IC & DESFire EV1 / EV2; (125 kHz & 13.56 MHz Dual Frequency) Module 2: ID & IC & DESFire EV1 / EV 2 & FeliCa & Legic & HID Prox (125 kHz & 13.56 MHz Dual Frequency) Module 3: ID & IC & DESFire EV1 / EV2 & FeliCa & Legic & HID Prox & HID iClass (125 kHz & 13.56 MHz Dual Frequency) Ingress Protection Rating: IP65 (waterproof and dustproof) IK04 (Vandal Resistant)
Dimension	195 mm*75 mm*25.35 mm (L*W*H)
Weight	Gross Weight: 1.13 Kg Net Weight: 0.52 Kg
Power Supply	Power Supply: DC 12V 3A Operating Temperature: -5℃ to 55℃ (23 ℉ to 131 ℉) Operating Humidity: 10% to 90% RH (Non-condensing)